

ADAM-4050 ADAM-4051 ADAM-4052

15-ch Digital I/O Module
16-ch Isolated Digital Input Module
with Modbus

8-ch Isolated Digital Input Module



ADAM-4050



ADAM-4051



ADAM-4052

Specifications

General

- Connectors 2 x plug-in terminal blocks (#14 ~ 22 AWG)
- Power Consumption 0.4 W @ 24 V_{DC}
- Watchdog Timer System (1.6 second)
- Supported Protocols ASCII command

Digital Input

- Channels 7
- Input Level Logic level 0: +1 V max.
Logic level 1: 3.5 ~ 30 V
Pull up current: 0.5 mA,
10 kΩ resistor to +5 V

Digital Output

- Channels 8
- Power Dissipation open collector to 30 V,
30 mA max. load
300 mW

Specifications

General

- Connectors 2 x plug-in terminal blocks (#14 ~ 28 AWG)
- Power Consumption 1 W @ 24 V_{DC}
- Watchdog Timer System (1.6 second) & Communication
- Supported Protocols ASCII command and Modbus/RTU

Digital Input

- Channels 16
- Input Voltage 50 V max
- Input Level Dry contact:
Logic level 0: open
Logic level 1: close to GND

Wet contact:
Logic level 0: +3 V max
Logic level 1: +10 ~ 50 V
(Note: Digital Input levels 0 and 1 can be inverted)
- Isolation Voltage 2500 V_{DC}
- Input Resistance 5.2 kΩ
- Overvoltage Protection 70 V_{DC}

Specifications

General

- Connectors 2 x Plug-in terminal blocks (#14 ~ 22 AWG)
- Power Consumption 0.4 W @ 24 V_{DC}
- Watchdog Timer System (1.6 second)
- Supported Protocols ASCII command

Digital Input

- Channels 8
(6 fully independent isolated channels, 2 isolated channels with common ground)
- Input Level Logic level 0: +1 V max.
Logic level 1: +3 ~ 30 V
- Isolation Voltage 5000 V_{RMS}
- Input Resistance 3 kΩ

Common Specifications

General

- Power Input Unregulated 10 ~ 30 V_{DC}

Environment

- Humidity 5 ~ 95% RH
- Operating Temperature -10 ~ 70 °C
(14 ~ 158 °F)
- Storage Temperature -25 ~ 85°C
(-13 ~ 185 °F)

Ordering Information

- ADAM-4050 15-ch Digital I/O Module
- ADAM-4051 16-ch Isolated Digital Input Module with Modbus
- ADAM-4052 8-ch Isolated Digital Input Module