

19" 2U Rackmount Industrial PC with 8th/9th Gen Intel® Core™ Processor, Max. 65W TDPs, Giga-LAN x 2

Industrial PC



## Features

- 8th /9th Gen. Intel® Core™ LGA1151 Processor
- DDR4 DRAM Support, 2666MHz, Max. 32GB
- M.2 Slot (M key) x 1, M.2 Slot (E key) x 1
- USB 3.2 Gen 1 Port x 4, USB 2.0 Port x 2
- Intel® Gigabit Ethernet x 2
- SATA 6.0 Gb/s x 2
- PCI-Express [x16] (Gen3) x 1
- Supports 400W ATX Single Power Supply




## Specifications

System	
Processor	8th/9th Gen. Intel® Core™ LGA 1151 socket Processor (formerly Coffee Lake-S), Max. 65W TDPs
Chipset	Intel® H310 Express Chipset
Memory	DDR4 2666/2400/2133 MHz SODIMM x 2, Up to 32GB, Non-ECC, Un-buffered Memory, Dual channel memory architecture
I/O Chipset	NCT6793D
Ethernet	Intel® PCIe Gb LAN 219V x 1, Intel® PCIe Gb LAN i210AT x 1
Audio	Realtek® ALC897 with Amp.
TPM	NPCT650 TPM2.0 (default: No)
Expansion Slots	PCIe3.0 [x16] x 1
BIOS	256Mbit Flash ROM, AMI BIOS
H/W Monitor	Temperature Monitor on CPU/Chassis, Voltage Monitor on Vcore/5V/12V, Fan Monitor on CPU/Chassis
WatchDog Timer	1~255 steps by software program
Smart Fan Control	CPU Fan/ Chassis Fan
Wake On LAN/ PXE	Yes (WOL / PXE)
Power State	S3, S4, S5
Graphics	
Graphics Chipset	Intel® UHD Graphics
Graphics Multi Display	HDMI+VGA, HDMI+DP, HDMI+LVDS, VGA+DP, VGA+LVDS, DP+LVDS
VGA	Up to 1920 x 1200 @ 60 Hz
DVI	—
HDMI	Up to 3840 x 2160 @30 Hz(HDMI 1.4b)
Display Port	Up to 4096 x 2160 @ 24 Hz / 3840 x 2160 @ 60 Hz
LVDS	LVDS Up to 1920 x 1200 @60 Hz, Dual Channel 18/24 bit (1 x inverter)
eDP	—
Backlight Control	—
Environment & Power & ME	
Battery	Lithium battery
Power Requirement	110-230 V AC Input
Operation Temperature	32°F ~140°F (0°C ~ 60°C)
Storage Temperature	-40°F ~185°F (-40°C ~85°C)
Operation Humidity	0%~90%RH, non-condensing
Certificate	BIS
Dimensions	
Weight	550mm x 435mm x 90mm (DxWxH)
Weight	8.5 Kg (approx)
MTBF (Hours)	333,520

Rear Panel I/O Ports	
USB	USB 3.2 Gen 1 (5 Gbps) x 4
Display I/O	VGA x 1, HDMI x 1, DP x 1
Audio I/O	Mic-in x 1, Line-out x 1
LAN I/O	LAN (RJ-45) port x 2
Serial Port	1x COM(RS485/422/232)
PS/2 Port	—
Others	—
Internal I/O Connectors	
Storage	SATA3.0 (6.0Gb/s) x 2, M.2 M-key (22 x 80mm) x 1
USB	USB 2.0 (2 x 5-pin, 2.00mm) x 1 port support additional 2 USB.
Display I/O	LVDS x 1
Audio I/O	AAFP x 1, Speaker x 1
Serial Port	Box header for COM (RS-232) x 1
PS/2 Port	—
Parallel Port	—
DIO	Digital I/O box header x 1
FAN	4-pin CPU Fan connector x 1, 4-pin Chassis Fan connector x 1
Power	—
Others	Front Panel connector x 1, Chassis Intrusion x 1, Buzzer onboard x 1, CMOS jumper x 1
OS	
OS Support	Windows® 10 64-bit, Linux Ubuntu 18.04 LTS


## Rear View



## Front View



## Block Diagram



## Ordering Information

Part number	CPU	RAM	Fan/Fanless	Display	Storage	LVDS	LAN	USB	RS-232	RS-232/422/485	Expansion Slot	Power	TPM	Temp.
TECH 2U 625	Socket	SODIMM x 2	Fan	VGA, HDMI, LVDS, DP	SATA3 x2, M.2(M-key)	1	GbE x 2	USB2.0 x 2 USB 3.2 Gen 1 x 4	1	1	PCIe3.0[x16] x 1	ATX	—	0-60°C